





# **bizhub** 4052

# Customer benefits



customised user interface

# Options


ENHANCED FEATURES
Upgrade kit UK-219
PDF enhancements LK-102v3
Barcode fonts LK-106
Unicode fonts LK-107
OCR A and B fonts LK-108
ThinPrint <sup>®</sup> client LK-111
ServerlessPullPrinting LK-114
Trusted Platform Module activation LK-115v2

2 CONNECTIVITY
USB I/F kit EK-P05
USB I/F kit
EK-P06
Wireless LAN UK-216
Biometric authentication AU-102
ID card reader
various ID card technologies
Interface cable for CSRC modem
EK-P07
Faxkit FK-517
Wireless LAN
SX-BR-4600






Secure network integration, data encryption, HDD overwrite, and advanced user authentication




Application ecosystem Enhanced efficiency thanks to Konica Minolta's extensive

Services Efficient printer fleet management, including automatic consumables delivery, pro-active maintenance and remote setup



5	MEDIA OUTPUT	
	Staple finisher FS-P02	





Finishing functionalities



# Descriptions

### bizhub 4052

A4 multifunctional with 40 ppm b/w. Standard Emperon™ print controller with PCL, PostScript and XPS support. Paper capacity of 550 sheets and 100-sheet manual bypass. Automatic dual-scan document feeder and duplex unit standard. 2 GB memory, 250 GB hard disk and Gigabit Ethernet.

### ENHANCED FEATURES

2 GB memory extension for upgrades
PDF/A (1b), PDF encryption, digital signature
Supports native barcode printing
Supports native Unicode printing
Supports native OCR A and B font printing
Print data compression for reduced network impact
Secure and Follow Meprinting solution require no server
application. Host devices require 4 GB memory.
Trusted Platform Module for protection of data encryption
and decryption

CONNECTIVITY	
EK-P05USBI/Fkit	USB keyboard connection
EK-P06USBI/Fkit	USB keyboard connection, Bluetooth
UK-216 Wireless LAN	Wireless LAN and wireless LAN Access Point Mode
AU-102 Biometric authentic	ation Finger vein scanner
ID card reader	Various ID cardtechnologies
FK-517 Fax kit	Super G3 fax; digital fax functionality
EK-P07 Interface cable	GPRS modem connection for CSRC
for CSRC modem	
SX-BR-4600 Wireless LAN	Wireless LAN to network connector
OTHERS	
CU-203 Air cleaning unit	Improving indoor air quality by reduced emissions
KP-10110-Keypad	For use instead of touchscreen
KP-10110-Keypad MEDIA INPUT	
MEDIA INPUT	For use instead of touchscreen
MEDIA INPUT PF-P15Papertray	For use instead of touchscreen A5–A4, 250 sheets, 60–120 g/m <sup>2</sup>
MEDIA INPUT PF-P15Papertray PF-P16Papertray SCD-4000e Copier desk	For use instead of touchscreen A5–A4, 250 sheets, 60–120 g/m <sup>2</sup> A5–A4, 550 sheets, 60–120 g/m <sup>2</sup>
MEDIA INPUT PF-P15Papertray PF-P16Papertray	For use instead of touchscreen A5–A4, 250 sheets, 60–120 g/m <sup>2</sup> A5–A4, 550 sheets, 60–120 g/m <sup>2</sup>

# **Technical specifications**

Panel size/resolution	7" / 800 x 480
System memory (standard/max)	2 GB/4 GB
System hard disk	250 GB (standard)
Interface	10/100/1,000-Base-T Ethernet; USB2.0;
	Wi-Fi 802.11b/g/n (optional)
Network protocols	TCP/IP (IPv4/IPv6); SMB; LPD; IPP; SNMP; HTTP; HTTPS
Automatic document feeder	Up to 50 originals; A6–A4; 52–120 g/m <sup>2</sup> ;
	automatic dualscan document feeder
Printable paper size	A6–A4; customised paper sizes
Printable paper weight	60-216 g/m <sup>2</sup>
Paper input capacity (standard	l/max) 650 sheets/2,300 sheets
Paper tray input (standard)	550 sheets; A6 – A4, 60 – 120 g/m <sup>2</sup>
Paper tray input (optional)	3x 250/550 sheets; A5–A4; 60–120 g/m <sup>2</sup>
Manualbypass	100 sheets; A6-A4; custom sizes; 60-216 g/m <sup>2</sup>
Automatic duplexing	A4; 60–90 g/m²
Finishing modes	Group/sort; staple (optional)
Output capacity	Max.: 250 sheets
Stapling (optional)	Max.: 20 sheets
Copy/print volume (monthly)	Rec.: 7,000 pages
	Max.1: 100,000 pages
Tonerlifetime	25,000 pages
Imagingunitlifetime	60,000 pages
Powerconsumption	220-240 V/50/60 Hz; Less than 600 W
System dimensions (W x D x H)	490 x 521 x 546 mm
System weight	Approx. 24 kg (without options)

#### 600 x 600 dpi; 1,200 x 1,200 dpi Printresolution Page description language PCL 6 (XL 3.0); PCL 5; PostScript 3 (CPSI 3016); XPS Operating systems Windows 7 (32/64); Windows 8/8.1 (32/64); Windows 10 (32/64); Windows Server 2008 (32/64); Windows Server 2008 R2; Windows Server 2012; Windows Server 2012 R2; Windows Server 2016; Macintosh OS X 10.9 or later; Linux; Unix; Citrix Printer fonts 80 PCL Latin; 137 PostScript 3 Emulation Latin Print functions Direct print of TIFF; XPS; PDF (v1.7) and OOXML (DOCX, XLSX, PPTX); secure print; proof print; overlay; n-up; booklet page order; watermark Mobile Printing AirPrint (iOS), Mopria (Android), Konica Minolta Print Service (Android), Konica Minolta Mobile Print (iOS, Android & Windows 10 Mobile); Mobile Authentication and Pairing (Android &iOS) optional: Google Cloud Print; Wii Direct SCANNER SPECIFICATIONS Scan speed (mono/colour) Up to 47/30 ipm in simplex Up to 94/60 ipm in duplex Scan resolution Up to 600 x 600 dpi

Scanmodes	Scan-to-eMail (Scan-to-Me); Scan-to-SMB (Scan-to-Home);	
	Scan-to-FTP; Scan-to-HDD; Scan-to-USB; Scan-to-WebDAV;	
	Scan-to-URL; Network TWAIN scan	
File formats	TIFF, PDF, Compact PDF, JPEG, XPS, PDF/A (opt.), Compact	
	XPS, PPTX, Linearized PDF, Encrypted PDF	
Scandestinations	2,100 (single + group); LDAP support	
Scan functions	Up to 400 job programs	

### PRINTER SPECIFICATIONS

# DATASHEET bizhub 4052

### COPIER SPECIFICATIONS

Copyingprocess	Electrostatic laser
Copy/print speed A4	Up to 40 ppm
Autoduplex speed A4	Up to 30 ppm
1st copy out time	6.5 sec.
Copyresolution	600 x 600 dpi
Gradation	256 gradations
Multicopy	1–9,999
Original format	Max.A4
Magnification	25-400% in 0.1% steps; auto-zooming
Copy functions	Electronic sorting; multi-job; adjustments (contrast,
	sharpness, image density); proof copy; interrupt mode;
	separate scan; sort/group; combination; original selection;

ID card copy; 2-in-1; 4-in-1; 8-in-1

## FAX SPECIFICATIONS

Fax standard	Super G3 (optional)
Faxtransmission	Analogue; i-Fax
Fax resolution	Up to 600 x 600 dpi (ultra-ine)
Fax compression	MH; MR; MMR; JBIG
Faxmodem	Up to 33.6 Kbps
Faxdestinations	2,100 (single +group)
Faxfunctions	Timeshift; PC-Fax; fax forwarding; up to 400 program dials

### SYSTEM FEATURES

Security	ISO15408 Common Criteria (in evaluation); IP iltering and
	port blocking; SSL2; SSL3 and TLS1.0 network communication; IPsec support; IEEE 802.1x support; user authentication;
	secure print; Kerberos; hard disk overwrite (8 standard types);
	hard disk data encryption; copy protection (print only)
Accounting	Up to 1,000 useraccounts;
	Active Directory support ID card authentication optiona
Software	PageScope Net Care Device Manager; PageScope Web
	Connection; Print Status Notiier; Driver Packaging Utility

 $^{\rm 1}$  lf the maximum volume is reached within a period of one year, then a maintenance cycle must be performed

- <sup>2</sup> Warm-up time may vary depending on the operating environment and usage
- All specifications refer to A4-size paper of 80 g/m<sup>2</sup> quality.
  The support and availability of the listed specifications and functionalities varies depending on operating
- The stated life expectancy of each consumable is based on specific operating conditions.
  The stated life expectancy of each consumable is based on specific operating conditions such as page coverage for a particular page size (5% coverage). The actual life of each consumable will vary depending on use and other printing variables including page coverage, page size, media type, continuous or intermittent printing, ambient temperature and humidity. – Some of the product illustrations contain optional accessories.
- Specifications and accessories are based on the information available at the time of printing and are subject to change without notice.
- Konica Minolta does not warrant that any specifications mentioned will be error-free.
- All brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

GmbH · Europaallee 17 · 30855 Langenhagen · Germany · www.konicaminolta.eu

Telecopy Sp. z o.o. Wrocław tel. 717957717 tel. 717957718



